



2	Pin	Copper	Sn Plated
1	Housing	LCP	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准	UL Standard:	B	C D
额定电压/电流	/Rated Voltage(V)/Current(A)	300/8	50/8 /
EC 标准	/EC Standard:		
过压类别	/Overvoltage Category/污染等级	III/3	II/2 II/2
污染度	Degree		
额定电压/电流	/Rated Voltage(V)/Current(A)	200/9.5/250/9.5	320/9.5
额定脉冲电压	(KV)/Rate Impulse Voltage(KV)	2.5	2.5 2.5
间距/Pitch(mm)	/线数范围/ Poles	3.5/N=04~48P	
使用温度范围	/Operating temperature(°C)	-40~+130	
符合RoHS环保要求	/Conform to RoHS	Yes	

MATERIAL:		SURFACE:	
MATERIAL:		SURFACE:	
MAT NO.:			
STATUS:			
APPD:			
CHKD:			
DRT:			



NAME: 15ESAVHC-THR-3.5-XXP-1Y-00A(H)  
DRAWING NO.:  
SCALE: 1/1

公差 (General tolerances)(mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	~	~	~	~	~	~	~	~	~	~	~	~	~
	3	6	10	18	30	50	80	120	180	250	315	400	500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.50

公差 (General tolerances)(mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	~	~	~	~	~	~	~	~	~	~	~	~	~
	3	6	10	18	30	50	80	120	180	250	315	400	500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.50

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	
mm	
(inch)	
TYPE:	
SCALE:	
SHEET	
REV	
1/1	



NAME: 15ESAVHC-THR-3.5-XXP-1Y-00A(H)  
DRAWING NO.:  
SCALE: 1/1