



2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)	300/15	/	300/10
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	VDE 标准/VDE Standard:		
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	400/20
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	/	4
间距/Pitch(mm)/线数范围/Poles	7.62/N=02~12P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

SURFACE:

 **宁波三安电子科技有限公司**
Sanan Electrical Technology Co., Ltd

NAME: **2ESAVC-7.62-XXP-1Y-100A(H)**

MATERIAL:
MAT NO.:
STATUS:
APPD:
CHKD:
DRT:

DRAWING NO.:
SCALE:
SHEET: 1/1

公差/General tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
	±Z	±Z	±Z	±Z	±Z	±Z	±Z	±Z	±Z	±Z	±Z	±Z	±Z	±Z

DRAWING NO.:
SCALE:
SHEET: 1/1